

CHARGEURS PCC

FASHION TECHNOLOGIES

LADIESWEAR · MENSWEAR · KIDSWEAR · PERFORMANCE · ECO-SOLUTIONS

SFK50/A25

CONSTRUCTION
COMPOSITION
COATING
WEIGHT
WIDTH
COLOURS
DOPE DYED
COLOR DOT
APPLICATION

Jersey
100.0 % Recycled polyester
Polyamide - 23 mesh
48.0 gr/m²
150 cms
Natural , Black , Non Optical White NOW , Non Optical Black NBK , White

WOMENS AND MENS WEAR

Blouses
Dresses
Jackets - Blazers
Pants
Pants - Skirts
Waistbands

CARE INSTRUCTIONS



	Fusing Conditions	
 Glueline temperature	116/132 C	116/132 C
 Ironing	200/400 gr/cm	2/4 bar
 Time	12/15 s	12/15 s

In view of the wide variety of existing fabrics and other materials used by the clothing industry, Lainière de Picardie recommends that before industrial use, complete tests are carried out with the fabrics and other materials to be used, and on the machines that will be used. Lainière de Picardie guarantee is, explicitly limited to the replacement of any of its products recognised to be defective, to the exclusion of all other compensation or damages.



Class I



AMERICAS · EUROPE · MIDDLE EAST · AFRICA · ASIA PACIFIC

www.chargeurs-pcc.com